

MOTOROLA WS2000

WIRELESS SWITCH

ISIS
integration

All-in-one wired and wireless switch for small to medium sized business and branch offices



Simple, cost-effective wired and wireless networking for enterprise branch offices

The WS2000 Wireless Switch is a powerful all-in-one solution that simplifies and reduces the costs of managing wired and wireless (802.11a/b/g) networks in enterprise branch offices. The integrated router, gateway, firewall, Power-over-Ethernet (PoE) and more eliminate the cost of purchasing and the complexity of managing multiple pieces of equipment. Support for Wi-Fi Multimedia extensions (WMM) enables the WS2000 to provide peak performance for even the most demanding applications, including voice and video. The ability to easily and cost-effectively scale to meet growing needs, as well as upgrade to support new security, radio and other standards provides the assurance that the WS2000 will meet your needs today and tomorrow. The WS2000 - enterprise-class networking functionality, priced for the small to medium-sized business or enterprise branch office.

End-to-end enterprise-class security

Protect your network and data with end-to-end enterprise-class security with support for WPA2, an integrated AAA (authentication, authorisation and accounting) server for authenticating users, Rogue Access Port/Point (AP) detection, Stateful Packet Inspection Firewall and more. Your network resources are safe - only authorised users are granted access to your network. With the WS2000, your network perimeter and your resources are more secure.

Easy to manage and deploy

The WS2000 offers a level of management simplicity and flexibility that eliminates the need and cost for onsite IT personnel to manage the wireless networks. Less technical onsite staff in restaurants, retail stores, warehouses and healthcare clinics can easily manage the wired and wireless network through an intuitive web-based interface and centralised management and control of Access Ports. For larger corporations deploying the WS2000 in branch offices,



FEATURES

Switch-based centralised upgradeable architecture

802.11a/b/g compatibility

Wi-Fi Multimedia (WMM) extensions support

SIP Call Administration Control

Enterprise-class security: 802.1X/EAP Kerberos, WPA2 (802.11i)

Active/standby configuration

AAA integrated server: verifies identify of users and administrators

Integrated secure gateway: routing, DHCP, NAT, Stateful Packet Inspection Firewall and WAN uplink (with PPPoE support)

IP Filtering

Comprehensive features to enable public hot spots

Rogue AP detection

IPSec VPN

802.3af Power-over-Ethernet (PoE) Support

BENEFITS

Enhanced performance and functionality; simplified deployment/management, investment protection; low TCO

Lower cost; broad, flexible radio support

Enables voice/video applications with wired QoS extension support

Controls the number of active SIP sessions that are initiated by a wireless VoIP phone

Enterprise-class authentication and encryption; ensures privacy of data during transmission

Robust network redundancy through multiple links

Eliminates the cost/need to manage a separate RADIUS server

Eliminates need to purchase and manage additional equipment; simplifies provisioning of network services

Provides flexibility in defining access policies.

Provides secure public access —complementary or service-based

Identifies and reports unauthorised access ports and points

Cost-effective secure point-to-point communications

Eliminates need and expense to power Access Points

secure remote management capabilities (with SSH and SNMP v3 support) and auto deployment capabilities (with DHCP options) enable staff in the centralised network operations or data center to easily control and manage devices anywhere in the world. Implementation is fast and easy: the plug-and-play WS2000 automatically detects and configures Access Ports with the best channel. And tight integration with the wired network simplifies the extension of wired virtual LANs (VLANs), improving network performance as well as providing added protection against unauthorised access.

Ideal for hotspots

The WS2000 is uniquely suited for hotspots, enabling hotels, airports, lounges, restaurants and more to offer

WS2000 Specifications

Packet Forwarding

802.1D-1999 Ethernet Bridging; 802.11-.802.3 Bridging

Wireless Networking

Wireless LAN: Supports 8 WLANs; Virtual AP - Multi-ESS/BSSID traffic segmentation; Pre-emptive Roaming; Automatic Load Balancing

VLAN Support: Wireless LAN to VLAN mapping; auto assignment of VLANs based on user authentication

Access Port Radios: Supports 1-6 802.11a/b/g Access Ports; Automatic Access Port Adoption with ACLs; Auto Channel Selection capability

Radio & Frequency Management: Dynamic Frequency Selection and Transmit Power Control (TPC); Country Code based RF Configuration

Network Security

Packet Filtering: L2/3/4 Stateful Packet Analysis; Network Address Translation (NAT)

Authentication Mechanisms: Access Control Lists (ACLs); Pre-Shared Keys (PSK); 802.1x/ EAP —Transport Layer Security (TLS), Tunneled Transport Layer Security (TTLS), Protected EAP (PEAP); Kerberos; Integrated AAA server with native support for PEAP and TTLS

Transport Encryption: WEP 40/128 (RC4), KeyGuard, WPA—TKIP, AES—CCMP; (802.11i/WPA2)

Key Exchange Management : Extensible Authentication Protocol (EAP) Kerberos

Rogue AP Detection: AP scanning on one or all channels; Motorola mobile client assist

IP Filtering: Configurable incoming and outgoing IP filtering policies on packets within the same subnet/WLAN and between wired and wireless hosts

Optimized Wireless QoS

Voice Prioritization; wireless bandwidth management; Power Save Protocol (PSP) integration; Wi-Fi Multimedia Extensions (WMM)

Management

Command Line Interface (Serial, Telnet, SSH); Admin authentication via Radius server; Java Applet (HTTP, Secure HTTP); Syslog; Text-Based Configuration Files; Remote configuration and firmware update (via TFTP, FTP); automatic update of configuration and firmware via DHCP options; SNMP v1/v2/v3; MIBs—MIB-II, Ping MIB, TraceRoute MIB, Motorola MIB

High Availability

Active/standby configuration support

visitors convenient anywhere anytime access to the Internet, email, and corporate applications. Support for authentication and Radius accounting enables organisations and service providers to offer secure wireless public access, either as a complimentary service, or an additional revenue stream.

Lower Total Cost of Ownership (TCO)

The WS2000 eliminates the complexities and reduces the costs associated with deploying, managing, securing, upgrading and scaling your wired and wireless network - delivering outstanding investment protection and a lower TCO. Symbol Enterprise Mobility Services provide the comprehensive support and technical expertise you need to design, deploy and maintain the most successful mobility solutions.

Physical Characteristics

Form Factor: Standard 1RU

Dimensions: 44.5 mm H x 286 mm W x 203 mm D

Weight: 0.64 kg

Physical Interfaces: 1 - RS232 serial console port
7 - 10/100 Ethernet ports (including 1 WAN uplink port),
4 Ports support 802.3af Power-over-Ethernet CF Card (for storage)
>50,000 Hours

MTBF: Yes

RoHS Compliant: Yes

Power Requirements

AC Input Voltage: 100-250 VAC

Max AC Input Current: 3A@230 VAC

Max Power Consumption: 120 W

Input Frequency: 47 Hz to 63 Hz

User Environment

Operating Temperature: 0°C to 40°C

Storage Temperature: -40°C to 70°C

Operating Humidity: 5% - 95% (w/o condensation)

Storage Humidity: 5% - 95% (w/o condensation)

Operating Altitude: 50 ft. to 8,000 ft./16 m to 2,438 m

Storage Altitude: 50 ft. to 12,000 ft./16 m to 3,658 m

Regulatory

Safety Certifications: UL, cUL (60950-1), EN60950-1, TUV/GS

EMI Compliance: FCC (Part 15 Subpart B), VCCI, EN 55024, EN 61000-3-2, EN 61000-3-3, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11

Part Numbers

WS-2000-SME-WWR

WS-2000-1C-ABG-WWR (WS2000 and 1 AP300 (802.11a/b/g) bundle)

WS-2000-2C-ABG-WWR(WS2000 and 2 AP300 (802.11a/b/g) bundle)

WS-2000-2C-BG-WWR (WS2000 and 2 AP300 (802.11b/g) bundle)

Specifications are subject to change without notice.

Contact Details

Isis Integration Ltd
6 Cantelupe Mews
Cantelupe Road
EAST GRINSTEAD
RH19 3BG

Tel: 01342 410542
Email: info@isisi.co.uk
Web: www.isisi.co.uk